

# Amighini Architectural

## WOOD DOOR LIMITED WARRANTY

AMIGHINI.NET

All Architecturals New Jersey LLC dba Amighini Architectural wood products are warranted for the time period set forth below, subject to the restrictions and conditions which follow. Wood doors are warranted to be of sound material and workmanship and to be free of defects, which would cause the door to be unfit for the ordinary recommended use for a period of one (1) year for exterior doors from the date of original purchase subject to the conditions and restrictions listed below and five (5) years for interior doors from the date of original purchase subject to the conditions and restrictions listed below. This limited warranty is extended to all end users of Architecturals New Jersey LLC. in which the door is used for normal entry purposes. If a door is determined to be defective and or damaged, and after an investigation is conducted by Architecturals New Jersey LLC we reserve the right to: 1 - Repair the door, or 2 - Provide a replacement part or parts for the door, or 3 - Provide a replacement door, or 4 - Refund the purchase price.

Architecturals New Jersey LLC WILL NOT BE RESPONSIBLE FOR CUSTOMER APPLIED FINISHES, INSTALLATION COSTS, OR ANY OTHER WORK NECESSARY FOR THE REPLACEMENT OF ANY DOOR OR WINDOW.

Exclusions to your Limited Warranty:

A) Custom doors more than 8' tall or 3'6" wide. B) Custom French doors or one-panel wood doors over 7' tall or 3' wide, unless used with multipoint hardware in which case doors not to exceed 8' tall are covered by this Warranty. C) Custom doors that have warpage, which does not exceed 1/4" in the plane of the door that have warpage which does not exceed 1/4" across the plane of the sash. Warpage is any distortion in the door itself and does not refer to the relationship of the door to the jamb or frame in which it is hung. The term "warpage" shall include bow, cup and twist. In measuring the amount of warpage in a door, the following method shall be used: Bow, cup and twist shall be measured by placing a straightedge on the suspected concave face of the door at any angle (i.e. horizontally, vertically, diagonally), with the door in its installed position. The measurement of bow, cup and twist shall be made at the point of maximum distance between the bottom of the straightedge and the face of the door. If the claimed defect is warpage, Architecturals New Jersey LLC may defer repairing or replacing the door for a period of up to twelve (12) months from the date of claim or the date when the door was installed, in order to permit conditioning and equalizing to humidity and temperature conditions. The deferral period will not be counted against the limited warranty period. D) Improper installation or failure to maintain your door. E) Doors less than 1 3/4" thick for exterior use. F) Doors, which have not been properly sealed on all six sides, within fourteen (14) days of delivery, including the top and bottom edges of the door or window. G) Damage caused by not complying with Architecturals New Jersey LLC "Handling, Finishing, and Installation Instructions." H) Damage caused by others or by any cause beyond the control of Architecturals New Jersey LLC., including but not limited to damage caused by misuse, abuse, accident, mishandling, or by fire, flood, earthquake, storm, tornado, or other acts of nature. I) Misuse of a door including but not limited to, using a door on a part of a building without providing adequate overhang or an appropriate finishing color. Adequate overhang depends on the typical weather conditions of the site where the building is located, but typically means an overhang projecting a distance away from the door at least equal to one half the elevation difference between the bottom of the door and the base of the overhang structure. J) Damage due to trimming the door more than a 1/2" from the top or 1 1/2" from the bottom of the slab. K) Panel movement and shrinkage; the panels in your door are designed to "float" and will expand and contract in response to environmental conditions. L) The appearance of any customer applied finish. M) Due to the excessive heat build-up, any exterior door used with an unvented glass storm door. N) Doors painted Black (or any Architecturals New Jersey LLC) with any sun exposure.

It is our goal to provide quality products to all of our customers. Our items are hand crafted by gifted artisans. Slight variations in aesthetic detail and finish may occur, such as variations in color, texture and grain pattern of the wood.

### Handling, Finishing, and Installation Instructions.

All unfinished custom doors must be finished/sealed on all six sides within three (3) days of delivery or the limited warranty becomes void. 1. Entrance doors shall always be stored on edge, supported vertically (not leaning). Interior doors must be stored flat, in a clean, dry environment. 2. Doors shall not be exposed to excessive heat, dryness, humidity, or direct sunlight prior to finishing. 3. Handle door with clean gloves and do not drag doors across each other or other surfaces. 4. Deliver doors to the job site after plaster is dry. If doors are stored on the job site for more than one week, all edges must be sealed. 5. All hardware locations, preparations, and methods of installation must be appropriate for the specific door. 6. Prior to finishing, remove all handling marks with 150 grit or finer sandpaper and remove all sanding dust. 7. Apply sealer, primer, or first coat of required finish immediately after fitting, cutting for hardware, weather stripping, etc. and before the installation of hardware or hanging the door. 8. All exposed surfaces of the door must be sealed, including the top, bottom, side edges, and the hardware cutouts. 9. Use only oil-based stains, sealers, or primers on the door. If water-based paint is to be used, it must be applied over an oil-based primer. (Note of Caution: An interior grade lacquer is NOT a satisfactory product for exterior use.) 10. All exterior surfaces, including the top, bottom, and sides of the door must be finish coated with a good quality exterior grade paint or varnish. At least three (3) coats of exterior grade varnish with a UV Inhibitor must be applied. 11. In order not to induce warpage or excessive deterioration of your door, avoid using dark stains or paints on the door surfaces exposed to direct sunlight. 12. Most finishes on exterior doors deteriorate relatively quickly. To insure exterior doors receive the protection required, inspect the condition of exterior finish at least once a year and refinish as often as needed to maintain the protective stability of the finish.

### Important Information About Warranty

Do NOT cut, trim or finish a door, sidelite or transom sash, before it has been fully inspected. Once the product has been cut and/or finished, it can not be returned to Architecturals New Jersey LLC for replacement unless it is defective in a way that is covered by the warranty. Please comply with all of the handling and finishing instructions completely to validate the warranty. The product must be hand sanded before finishing. There are no warranties that extend beyond the preceding. Architecturals New Jersey LLC shall not be liable for consequential, indirect, or incidental damages or for any amount in excess of the manufacturer's price for the shipment involved, whether the claim is for breach of warranty or negligence.

Architecturals New Jersey LLC insulated glass units will be warranted against seal failure only if installed in the unit by Architecturals New Jersey LLC. Flaws in the glass will follow the "eleven foot rule" This means that " A blemish shall not be detectable at a distance greater than eleven feet, when looking at the glass perpendicular to it using daylight or with background light suitable for observations of the blemishes.

Claims under this Limited Warranty must be made in writing within the period of this warranty and prior to the beginning of any repair work to: Customer Services, Architecturals New Jersey LLC., 246 Beacon Ave, Jersey Coty, NJ 07306. Claims must detail the date and location of purchase, THE NATURE OF THE PROBLEM, and the name, address and telephone number of the person making the claim. Architecturals New Jersey LLC reserves the right and must be given at least a thirty (30) day opportunity to have any door which is the subject of a warranty claim field inspected by an Architecturals New Jersey LLC representative.

**THIS LIMITED WARRANTY EXTENDS ONLY TO THE ORIGINAL PURCHASER OF PRODUCTS OR TO THE ORIGINAL PURCHASER OF THE STRUCTURE INTO WHICH SUCH PRODUCTS ARE INSTALLED.**

This Limited Warranty sets forth Architecturals New Jersey LLC'S maximum liability for its wood products. Architecturals New Jersey LLC makes no other warranty, expressed or implied, including implied warranties of merchantability and fitness for a particular purpose, with respect to its products except as set forth above. No distributor, dealer or representative has the authority to change or modify this Limited Warranty. In no instance shall Architecturals New Jersey LLC be responsible for indirect, consequential or incidental damages.

This warranty gives you specific legal rights, and you may have additional rights which vary from state to state. Some states do not allow the exclusion or limitation of implied warranties or of incidental or consequential damages, so the limitation or exclusion may not apply to you. **IN SUCH CASE, THE DURATION OF ANY IMPLIED WARRANTY SHALL BE THE SAME AS THAT OF THE EXPRESSED WARRANTY STATED HEREIN.**

Important Notes About Overhangs:

The wood door or entryway system must be installed in a protected opening which projects out a distance from the structure no less than one-half of the elevation difference between the lowest edge of the door and base of the overhang's highest point above the entryway with adequate roof overhang to protect the door and entryway. Damage may result from exposure due to installation in an unprotected opening, such as an installation without sufficient roof overhang protection. This will cause the door and/or entry system to be exposed to an unusual amount of direct sunlight and/or precipitation, which will result in the failure of the door or entryway. This damage is specifically not covered by the manufacturer's warranty. See illustrative sketch for explanation.

